

# PWX15-300



Line	Parameter	Value	Units	QC Limits
1	RMSE-free	0.38	Ohms	
2	Fs	40.12	Hz	
3	Re	5.50	Ohms	
4	Res	38.71	Ohms	
5	Qms	4.47		
6	Qes	0.63		
7	Qts	0.56		
8	L1	0.80	mH	
9	L2	1.37	mH	
10	RZ	4.45	Ohms	
11	RMSE-load	0.53	Ohms	
12	Vas(Sd)	169.89	liters	
13	Mms	95.18	grams	
14	Cms	105	µM/Newton	
15	D1	14.42	Tesla-M	
16	SPLref(Sd)	95.0	dB[0 ohms]	
17	Rub index	0.01		

Method: Mass loaded (75.500 grams)      Area (Sd): 855.30 sq cm  
 DCR mode: Fixed (6.00 0.50 ohms)      QC file: CLOSED

Nominal diameter : 38cm (15")  
 Nominal impedance : 8 ohm  
 Power RMS : 300 Watt  
 Sensitivity (1W/1m) : 96dB (+/-3dB)  
 Frequency Range : 43-3000 Hz  
 Voice coil diameter : 75,5mm  
 Overall diameter : 385mm  
 Cutout diameter : 355mm  
 Net Weight : 5,75kg

